



TYPE #	Chain (Ø)		Anchor Weight (max)		Breaking Strength		Case Ax B (mm)	Anchor side CxDxE (mm)	Angle (max)
	mm	inch	kgs	lbs	kgs	lbs			
<b>US06</b>	6	1/4"	13	29	2250	4960	Ø 35x110	Ø 10x16x31	30°
<b>US08</b>	8	5/16"	23	51	4150	9140	Ø 40x132	Ø 12x19x36.5	30°
<b>US10</b>	10	3/8"	36	80	6620	14580	Ø 45x150	Ø 14x21x40	29°
<b>US13</b>	13	1/2"	60	130	12000	26400	Ø 55x189	Ø 16x26x51.5	28°
<b>US16</b>	16	5/8"	100	220	18200	40000	Ø 65x224	Ø 20x30.5x59	28°
<b>US20</b>	20	3/4"	200	440	28500	63000	Ø 80x276	Ø 24x38x72	28°



Quickline USA  
 Warehouse  
 15581 Computer Lane #A  
 Huntington Beach, CA 92649  
 714-843-6961 x 210  
 714-843-6906 FAX

Show Room Offices  
 8700 Warner Ave #110  
 Fountain Valley, CA 92708  
 www.Quickline.us  
 info@quickline.us